


GaAs MMIC broadband amplifier chip, 2-20 GHz

Performance characteristics

- Frequency Range: 2 - 20 GHz
- Small signal gain: 19dB
- Gain flatness: ± 2.0 dB
- P -1 dB: 20dBm
- Psat : 21dBm
- Power supply: +5 V /140mA
- 50Ohm input / output
- Chip size: QFN 4X4

Block Diagram



Product Introduction

GPA-0220-22-CQ4 is a broadband amplifier chip with a frequency range of 2GHz~20GHz, a small signal gain of 19dB, and a P-1 output of 20dBm. GPA-0220-22-CQ4 is powered by a single +5V power supply. This chip is packaged in a 4 x 4 mm ceramic surface mount package, and the surface of the pin pad is gold-plated, which is suitable for reflow soldering installation.

Use limit parameters

Maximum drain voltage	+7V
Maximum input power	+20dBm
Operating temperature	-55 ~ +85°C
Storage temperature	-65 ~ +150°C

Exceeding any of these maximum limits may cause permanent damage.


Electrical performance parameters (TA = +25°C, Vd = +5V)

Index	Minimum	Typical Value	Maximum	Unit
Frequency Range	2-20			G Hz
Small Signal Gain	-	19	-	dB
Gain Flatness		± 2.0		dB
P -1dB	-	20	-	dBm
Psat	-	21	-	dBm
Input return loss	-	20	-	dB
Output return loss	-	15	-	dB
Quiescent Current		140		mA


GaAs MMIC Broadband Amplifier Chip, 2 - 20 GHz

Main index test curve


Gain vs. Frequency




Reverse Isolation vs. Frequency




Input Return Loss vs. Frequency




Output Return Loss vs. Frequency



P-1dB vs. Frequency




Psat vs. Frequency



GaAs MMIC Broadband Amplifier Chip, 2 - 20 GHz

Appearance structure



Top view

Bottom view


Side View

The units in the figures are all in millimeters , and the tolerance is ± 0.15 mm.

Pin Definition		
Bonding point number	Function Symbol	Functional Description
3	RFIN	RF signal input terminal, no DC blocking capacitor required
16	RFOUT	RF signal output terminal, no DC blocking capacitor required
20	VDD	Amplifier Drain Bias
2, 4, 15, 17	GND	The pins need to be well grounded to the RF and DC grounds
Chip bottom	GND	The bottom of the chip needs to be well grounded to RF and DC
other	NC	The pin is floating and can be grounded

GaAs MMIC Broadband Amplifier Chip, 2 - 20 GHz

Recommended Circuit



Raw material	Capacitance, inductance, resistance
C 1	100pF
C 2	100nF
C 3	2.2uF

Precautions for use

- Sealing material : Ceramic material that meets ROHS standards
- Lead surface plating: gold, gold layer thickness 0.30um MIN
- Maximum reflow peak temperature: 260 °C